

THE DOCUMENT COMPANY

XEROX

Xerox DocuTech®
Production Publishers

Specifications



DocuTech 6155 and 6180

are the first names in print on demand, and the last word in state-of-the-art performance.

The true value of DocuTech lies in its ability to help you work more productively. Speed counts.

And at up to 155 or 180 pages per minute, DocuTech 6155/6180 excel in that critical area. But they also have the ability to process multiple jobs at the same time, resulting in more jobs in less time.

It's your business...

powered by DocuTech.

Xerox DocuTech 6155 / 6180





For more information on the Xerox DocuTech® 6155/6180 Production Publishers, call **0800 787 787** or visit us on the Web at: www.xerox.co.uk

Xerox DocuTech 6155/6180 Production Publisher Specifications

Printer Control Module

- Sun Blade 2000
- Dual 900 MHz UltraSparc III processors
- 73 GB system disk
- 2 GB memory
- DVD-ROM Drive
- 17.4 inch colour flat panel display
- Keyboard and mouse
- Ethernet interface (10/100BaseT)
- Two image processing printer interface cards
- Controller stand (optional)

Printer Module

- Xerographic Engine.
- Print speeds:
 - DocuTech 6155: Up to 155 ppm. (A4)
 - DocuTech 6180: Up to 180 ppm. (A4)
- On-site upgrade is available for the DocuTech 6155*.
- Simplex or duplex printing.
- Enhanced 600 x 600 dpi laser raster output.
- ImageSense Technology.
- On-line, right and left side stitching/binding.
- 2 Tray Interposer (standard).
- 3 Tray Interposer (optional).

Throughput Materials

(Printing and finishing)

- Stock weights: 60 gsm bond to 200 gsm index.
- Sizes: 203 mm x 254 mm to 363 mm x 432 mm.
- Large format option available for 363 x 463.5 mm*.
- Lightweight paper option available for 50 gsm bond*.

Paper Input Capacity

(Sheet capacity all at 80 gsm)

- With Standard Interposer: 5 input paper trays with auto tray switching and document inserts.
 - Tray 1 1,100 sheets; 203 mm x 254 mm to 229 mm x 356 mm.
 - Tray 2 600 sheets; 203 mm x 254 mm to 229 mm x 356 mm.

- Tray 3 2,600 sheets of up to 363 mm x 432 mm.
- Tray 4 550 sheets, non-imageable, of up to 364 mm x 464 mm.
- Tray 5 2,600 sheets, imageable or non-imageable of up to 364 mm x 464 mm.
- Optional 3 Tray Interposer available*.

Paper Output Options

- Stacker: 3,000 sheets at 80 gsm.
Optional: 5,000 sheets at 80 gsm (with one High Capacity Stacker).
Optional: 10,000 sheets at 80 gsm (with two High Capacity Stackers).
- Stitcher: 2 – 70 sheets at 80 gsm
1 or 2 adjustable stitches.
- Binder: 15 – 125 sheets at 80 gsm.
 - Tape colours: Black, blue, red, brown, grey, white or green.
 - 425 11" binds per tape reel.
- SquareFold Booklet Maker (optional).
 - Fully automatic booklet making system.
 - All operator settings are made with the push of a few buttons.
 - Up to 22 sheets at 80 gsm or 26 sheets at 60 gsm.
 - Paper sizes:

	Width	Length
Min.	211 mm	279 mm.
Max.	297 mm	432 mm.
 - Cover Insertion Module (CIM) (optional).
 - Adjustable saddle stitch heads, folder, trimmer.
- Supports Level 1 Document Finishing Architecture (DFA).

Client Environments Supported

- Windows 95/98, NT, 2000, XP.
- Mac OS 7.6 and above.
- Sun OS 4.1.3 / Solaris 1.1.1B.
- Solaris 2.3 / 2.4 / 2.5.1 / 2.6 / 8.x.

PDLs and Data Formats

- Adobe PostScript Level 3/PDF.
- PCL 5e. • TIFF. • ASCII. • VIPP® Software.
- Optional LCDS

Native Network Environments

- TCP/IP. • AppleTalk. • Novell (SPX-IPX).

Electrical Requirements

- Printer Controller:
 - 100/240 VAC + 10%, 47-63 Hz, 0.875 KVA (max).
- Printer Module:
 - 380/440 VAC ± 10%, 3 phase STAR.
 - KVA Rating (typical – based on actual run testing of the machine): Standby: 1.5 KVA; Operating: 8.2 KVA.
 - Agency certification: UL 1950 IEC 950, CSA 22.2 – 950, FCC (Class A), EN55022 (Class A), CISPR22 (Class A), EN50082-1: 1992 (Generic Immunity Standard), and ICES003 (Class A).

Physical Characteristics

Width	Depth	Height	Weight
Printer Controller – Processor Module			
254 mm	610 mm	1455 mm	32 kg
Printer Controller – Controller Stand			
762 mm	762 mm	965 mm	76.8 kg
Printer Controller – 17.4" TFT Screen			
460 mm	240 mm	460 mm	27.7 kg
Printer Module (with Interposer)			
4545 mm	1165 mm	1240 mm	1458 kg

Please reference the Xerox DigiPath® Production Software Specification Sheet for complete DigiPath specifications.

*Contact your Xerox Sales Representative for more details.



©2002 XEROX Corporation. All rights reserved. XEROX®, The Document Company®, X® (stylised), DigiPath®, VIPP®, and DocuTech® are trademarks of or licensed to Xerox Corporation. Product appearance, build status and/or specifications are subject to change without notice. 04/03.

708P87151GBE

Xerox (UK) Ltd.
Bridge House
Uxbridge
Middlesex
UB8 1HS
0800 787 787
www.xerox.co.uk