



color laser printer

Small size,
great color,
exceptional value





Call today. For more information, call **1-877-362-6567** or visit us at **www.xerox.com/office**



Phaser 6130

Speed	Up to 12 ppm color / 16 ppm black-and-white
Duty cycle	Up to 40,000 pages / month ¹
Paper Handling	
Paper input	Tray 1: 250 sheets, Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 355.6 mm Manual Feed Slot: 1 sheet, Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 355.6 mm
Paper output	150 sheets
Print	
First-page-out time	As fast as 17 seconds color / 14 seconds black-and-white
Resolution (max)	600 x 600 x 4 dpi
Processor	333 MHz
Memory (std / max)	128 MB / 1,152 MB
Connectivity	10/100 Base-TX Ethernet, USB 2.0
Page Description Languages	PCL® 6 emulation, Adobe® PostScript® 3™
Print features	Skip blank pages, N-up, Fit to new page size, Booklet printing ² , Watermarks ² , Poster ² , Banner sheets ² , Secure Print ³ , Proof Print ³ , RAM collation ³
Warranty	One year on-site warranty, Xerox Total Satisfaction Guarantee

¹ Print volume uniformly distributed over 30 days
² Accessed via PCL driver
³ Requires minimum 256 MB RAM

Device Management

CentreWare® IS Embedded Web Server, CentreWare Web, PrintingScout®, Email alerts

Print Drivers

Windows® 2000/2003 Server/XP/XP Home Edition (SP1 or higher), Vista, Mac OS®X version 10.2 or higher, Linux: SUSE™ 9.2/9.3, Turbo Linux™ 10, Red Hat® ES3/ES4, Fedora™ Core 1, Yellow Dog 3.X

Font Support

PostScript® fonts: 136; PCL® fonts: 81

Media Handling

Media weights: 17–40 lb. bond to 80 lb. cover / 65–220 gsm
 Manual two-sided printing: 17–40 lb. bond / 65–164 gsm
 Media types: Plain paper, glossy coated, envelopes, labels, card stock, business cards

Maximum Printable Area

8.0 in. 13.5 in. (0.5 in. border)
 208 mm x 347 mm (5 mm border)

Color Standards

PANTONE® Color approved solid-color simulations, Xerox Color Correction, ICC Profile

Operating Environment

Temperature: Storage: 32° to 95° F / 0° to 35° C, operating: 50° to 90° F / 10° to 32° C
 Humidity: 15% to 80%
 Sound pressure levels:
 Printing: 51.6 dB(A)
 Standby: 25.7 dB(A)
 Sound power levels: Printing: 6.46 B, Standby: 4.30 B
 Warm-up time: 30 seconds or less

Electrical

Power: 110–127 VAC, 50/60 Hz or 220–240 VAC, 50/60 Hz
 Power consumption: Standby: <50 W
 Printing: 280 W
 Power save: 5 W or less
 ENERGY STAR® qualified

Dimensions (WxDxH)

15.75 x 15.51 x 15.3 in. / 400 x 394 x 389 mm
 Weight: 38 lb. / 17.2 kg

Package Dimensions (WxDxH)

21.1 x 20.4 x 22.2 in. / 543 x 518 x 565 mm
 Weight: 46.2 lb. / 21.0 kg

Certifications

FCC Part 15, Class B, Listed UL 60950-1/CSA 60950-1-03, CE Mark applicable to Directives 73/23/EEC and 89/336/EEC, Section 508 ADA

Supplies

Toner Cartridge¹:
 Black: 2,500 std. pages 106R01281
 Cyan: 1,900 std. pages 106R01278
 Magenta: 1,900 std. pages 106R01279
 Yellow: 1,900 std. pages 106R01280

¹ Average Continuous Composite CMY Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

Options

256 MB Phaser Memory 097S03743
 512 MB Phaser Memory 097S03635
 Multi-Protocol Network Card 097S03745
 Wireless Network Adapter 097S03740

